



WN Series

For corrugated and packaging trim and shredded material

Key Advantages:

- Single Tension Cylinder – the side and top channels are hinged – creating four way tension – 3x greater friction force than competitive designs – creating heavier bales
- Best Auto-tie is the industry featuring pull technology, pulling the opposite side wire to the twisting, cutting and knotting process. Tier unit is on castors so you can easily open the unit to inspect and adjust tier for more accurate tying.
- Subfloor System – all units are heavy construction with inner liner system on floor and ram bottoms - provides a much longer lasting design plus much less expensive to renew vs. the competition
- Category III Safety features – all standard
- Increase bale weights from 1400 pounds to 2200 pounds – means less material handling, wire cost, and wear (36% less)
- Increased surge capacity – with low separator situations –



5042WN Series

PRODUCTION OPTIONS

Models: 5042WN-10
Bale Size: 43" x 43" x variable
Main Cylinder: 10" bore trunnion design
System Pressure: 3000 psi
Main Motor: 30, 50, 75, Twin 30 or Twin 50HP
Feed Type: Air System
No shear, clearance baler
Meets all current ANSI 245.5 Safety Standards

Remote Floor Mounted Power Unit
Additional 4' Bale Tables
Bale Runout Sensor
Off-side tier controls
Hydraulic oil shipped in baler reservoir
Wire run out sensors
Increase accessory equipment controls up to 15HP
Water Mist (4 Nozzle)
Bulk Wire System



BEYOND THE EXPECTED