



WS Series

For OCC and other shredding applications

Key Advantages:

- Single Tension Cylinder – the side and top channels are hinged – creating four way tension – 3x greater friction force than competitive designs – creating heavier bales
- Best Auto-tie is the industry featuring pull technology, pulling the opposite side wire to the twisting, cutting and knotting process. Tier unit is on castors so you can easily open the unit to inspect and adjust tier for more accurate tying.
- Subfloor System – all units are heavy construction with inner liner system on floor and ram bottoms - provides a much longer lasting design plus much less expensive to renew vs. the competition
- Category III Safety features – all standard
- Shear Design – Heavy duty, shim-able, reversable, and replaceable – bolt in Serrated Blade – some competitors have



WS Series

PRODUCTION OPTIONS

Models: 42W and 48W

Bale Size: 43" x 43" x variable; 49" x 43" x variable

Main Cylinder: 8", 9" or 10" bore trunnion design

System Pressure: 3000 psi

Main Motor: 30, 50, 75 , Twin 30 HP or Twin 50 HP

Feed Type: Conveyor(s), loader, hand feed

Bale Tying: Five-wire auto-tie (Push Through Design)

Remote Floor Mounted Power Unit

Additional 4' Bale Tables

Bale Runout Sensor

AR300 Charge Box Side Sheets

Side Load Feed Hopper

(Flared One Side or Both Sides)

Off-side tier controls

Hi-Lo Multi-Height Floor

Hydraulic oil shipped in baler reservoir

Wire run out sensors

Increase conveyor controls up to 15HP

Water Mist (4 Nozzle)

Bulk Wire System

